

Dynapac DR7X Rammers



Technical data

| ŝ, | Masses | |
|--------|---------------------|----------------|
| | Net mass | 67 kg |
| | Operating mass (CE) | 68 kg |
| ٢ | Traction | |
| | Max. area coverage | 336 m² /h |
| | Max. working speed | 20 m/min |
| ₩ ₩ | Compaction | |
| | Impact force, kN | 17 kN |
| | Vibration frequency | 10.0 – 11.8 Hz |

| Engine | |
|---------------------------|---------------------|
| Manufacturer/Model | Honda GXR 120 |
| Number of cylinders | 1 |
| Туре | air cooled gasoline |
| Rated power | 2.8 kW |
| Fuel tank capacity | 31 |
| Fuel consumption /h, avg. | 0.9 |
| Drive system | |
| Drive system | Mechanical |


Find us locally at <u>www.dynapac.com</u>

We reserve the right to change specifications without notice. Photos and illustrations do not always show standard versions of machines. The above information is a general description only, all informations are supplied without liability.



Dynapac DR7X Rammers

Technical data



| Dimensions | |
|---------------------|---------|
| B. Width | 350 mm |
| H. Height | 1030 mm |
| L. Length | 728 mm |
| L1. Length | 335 mm |
| W. Basic shoe width | 280 mm |

Standard equipment

- Infinitely variable frequency
 Hour and rpm display
 Low vibration handle bar
- Multi stage fuel and air filter system
 Self-cleaning air filter housing
 Auto oil level check before start

- Engine protection covers
 Engine & fuel start/stop on the same switch
 Recoil starter
 Loading aid rollers on handle

One point lift



Puncture proof transport wheels
 Foot widths (160-330 mm)

- Foot extensions
- Service kit

Find us locally at www.dynapac.com

We reserve the right to change specifications without notice. Photos and illustrations do not always show standard versions of machines. The above information is a general description only, all informations are supplied without liability.