Dynapac CC5200C

Combi rollers





Technical data

Masses	
Max. operating mass	10900 kg
Operating mass (incl. ROPS)	10000 kg
Module mass (front/rear)	5600 kg/4400 kg

Traction	
Speed range (Dual/TC/AS)	0 -12
Vertical oscillation	±8°
Theor. gradeability	35 %

***************************************	Compaction	
	Wheel load	1100 (kg/wheel)
	Centrifugal force (high/low amplitude)	154/101 kN
	Nominal amplitude (high/low)	0.8/0.3 mm
	Static linear load	28.7 kg/cm
	Vibration frequency (high/low amplitude)	51/67 Hz
	Water tank volume	900/1150 I
	Emulsion tank	78 I

Engine	
Manufacturer/Model	Cummins QSB 4.5, IIIB/T4i
Туре	Water cooled turbo Diesel
Rated power, SAE J1995	97 kW (130 hp) @ 2200 rpm
Fuel tank capacity	240

Engine		
Manufacturer/Model	Cummins QSB 4.5, IIIA/T3	
Rated power, SAE J1995	93 kW (125 hp) @ 2200 rpm	


Hydraulic sy	Hydraulic system	
Driving	Axial piston pump with variable displacement. Axial piston motors (3) with variable displacement.	
Vibration	Axial piston pump with variable displacement. Axial piston motor with constant displacement.	
Steering	Gear pump with constant displacement.	
Service brake	Hydrostatic in forward and reverse lever.	
Parking/ Emergency brake	Failsafe multidisc brake in drum and wheel motors.	


Dynapac CC5200C





Technical data





Dimensions	
A. Wheelbase	3690 mm
B. Width	2138 mm
C. Curb clerance	865 mm
D. Drum diameter	1300 mm
H1. Height, with ROPS/cab	2990 mm
H2. Height, w/o ROPS/cab	2275 mm
K. Ground clearance	310 mm
L. Length	4990 mm
R. Turning radius, outside	5070 mm
S. Drum shell thickness	18 mm
W1. Drum width	1950 mm
W2. Width, wheel module	1652 mm
W3. Width, tyre	285 mm
W4. Wheel track	467 mm
W5. Wheel spacing	165 mm
α. Steering angle	±32°