Dynapac CP1200W

OYNAPAC

Pneumatic rollers



Technical data

Masses	
Operating mass (incl. ROPS)	5550 kg
Operating mass (incl. Cab)	5850 kg
Mass with max. ballast	12100 kg

Traction	
Transmission	Hydrostatic, direct drive motors at rear tyres
Theor. gradeability	30 %
Speed range	0 -18 km/h

Compaction	
Rolling width	2090 mm
Tyre overlap	48 mm
Wheel loads, without ballast	620 kg
Wheel loads, with max. ballas	t 1340 kg
Tyre pressure, min	240 kPa
Tyre pressure, max	630 kPa
Tyre type (smooth)	10.5-80, 14 ply
Water spray system, type	Pressurized, electric pump
Water spray system, tank cap	acity 350 I
Water spray system, spray no	ozzle one per tyre
Number of tyres	5 front, 4 rear
Wheel oscillation (°)	±3

Engine	
Manufacturer/Model	Cummins QSF 2.8 (Stage IIIB/Tier 4final)
Rated power, SAE J1995	55 kW (74 hp) @ 2200 rpm
Туре	Water cooled turbo Diesel
Fuel tank capacity	130 l
Electrical system	12 V

Engine		
Manufacturer/Model	Cummins QSB 2.8 (Stage IIIA/Tier 3)	
Rated power, SAE J1995	55 kW (74 hp) @ 2200 rpm	
Туре	Water cooled turbo Diesel	


Hydraulic s	system
Driving	Axial piston pump with variable displacement. Axial piston motors with constant displacement.
Steering	Gear pump with constant diplacement
Service brake	Hydrost. braking on drive wheels (rear)
Parking/ Emergency brake	Spring -applied on drive wheels (rear)

Dynapac CP1200W



Pneumatic rollers

Technical data



Dimensions	
A. Wheelbase	2760 mm
B. Width	1,990 mm
B1. Width	2,090 mm
H1. Height, with ROPS/cab	2950 mm
H2. Height, w/o ROPS/cab	2210 mm
K. Ground clearance	260 mm
L. Length	3660 mm
R. Turning radius, outside	7,090 mm

