Dynapac F80W

Mini pavers





Technical data

Masses	
Weight (incl. standard screed)	1.15 t

Dimensions	
Basic width	0.84 m
Transport length	2.52 m
Working width, min.	0.25 m
Working width, max.	1.65 m

Capacity	
Paving thickness (max/min)	5-100 mm
Theoretical placement capacity	35 t/h

Material hopper	
Capacity	0.6 m ³

Traction	
Paving speed	0-25 m/min
Transport speed	0-5 km/h

Engine	
Manufacturer/Model	Hatz 1B40
Rated power	6.3 kW
Туре	Air cooled
Electrical system	12 V
Fuel tank capacity	51

Undercarriage	
Final drive	Hydrostatic
Front wheels	1x 330/152
Rear wheels	2x 432/127
Turning radius (inside)	950 mm

E Conveyor	
Conveyor control	Automatic with limit switch and flow gates
Conveyor type	One conveyor, reversible


Auger	
Auger control	Automatic with limit switch
Auger diameter	120 mm


Dynapac F80W

Mini pavers



Technical data





Dimensions	
B. Width	0.84 m
H1. Height	1.52 m
H2. Height, operator platform	0.42 m
L1. Length	2.86 m
L2. Length, transport	2.52 m
L3. Length, hopper	1.67 m



- Mechanical extensions (2x 175 mm) till 1650 mm

- Twin wheels
 Hopper filling help
 Additional auger LED light
 Front wheel scraper

-1	Suitable screeds					
	Model	Basic width	Working width, hydraulic extendable	Working width, max.	Compacting elements	Heating system
	Dynapac V1300V	0.80 m	1.30 m	1.65 m	Vibration	Propane (LPG)