## Dynapac MF2500CS w. SwingApp



Mobile feeders



## **Technical data**

Dumping height, center

Masses	
Transport mass	24.50 t
Dimensions	
Transport length	14.30 m
Transport width	2.55 m
Transport height	3.10 m
Front ramp angle	10°
Material hopper	
Capacity	6.0 m <sup>3</sup>

Traction	
Operating speed, max	25 m/min
Transport speed, max	4 km/h

Engine	
Manufacturer/Model	Cummins QSB 6.7-C220
Rated power, SAE J1995	164 kW (220 hp ) @ 2200 rpm
Electrical system	24 V
Emissions according to	Stage 3A /Tier 3
Fuel tank capacity	300 I

Engine	
Manufacturer/Model	Cummins QSB 6.7-C225
Rated power, SAE J1995	168 kW (225 hp ) @ 2200 rpm
Electrical system	24 V
Emissions according to	Stage 4 /Tier 4f
Fuel tank capacity	300 I

Conveyor	
Conveyor type	Rubber belt on two chains, mounted with metal stiffeners
Conveyor speed	Constantly variable
Conveyor width	1.20 m
Feeding height (max/min)	3.4 m /1.1 m
Feed capacity	4000 t/h
Feed capacity, optional swing conveyor	2000 t/h


525 mm


## Dynapac MF2500CS w. SwingApp



Mobile feeders

## **Technical data**





Dimensions	
A. Axle track	3.90 m
B1. Width, max.	3.35 m
B2. Width, standard	2.55 m
B3. Width, wheel track	2.09 m
C1. Track width	0.57 m
H1. Height, max.	4 m
H2. Height, transport	3.10 m
H3. Height	0.57 m
L1. Length	14.30 m
L3. Length, hopper	2.29 m