Dynapac DRP60D

OVNAPAC

Plate compactors



Technical data

Masses	
Basic mass	560 kg
Operating mass (W)	570 kg
Operating mass (W1)	547 kg
Operating mass (W2)	585 kg

Traction	
Max. gradeability	35 %
Max. working speed	28 m/min

Compaction	
Frequency	66 Hz
Centrifugal force	70 kN
Amplitude	1.80 mm

Engine		
Manufacturer/Model	Hatz 1D 81	
Emissions according to	Stage V /non EPA	
Туре	Air cooled, diesel	
Number of cylinders	1	
Fuel consumption /h, avg.	2.0	
Fuel tank capacity	10 I	
Power	9.3 kW @ 2700 rpm	


Drive system	
Drive system	Mechanical

Dynapac DRP60D





Technical data



Dimensions		
H. Height	910 mm	
H1. Height	1180 mm	
H2. Height	1540 mm	
L. Length	1860 mm	
L1. Length	980 mm	
W. Basic plate width	700 mm (75 + 550 + 75)	
W1. Plate width, without extensions	550 mm	
W2. Plate width, with extensions	850 mm (150 + 550 + 150)	



- Control handle -comfort -with vibration isolation
 Height adjustable control lever
 Control lever lock in transport and working position
- Reverse drive protection
- Highly wear resistant base plate
 All around protection hood
 All around protection for V-belt

- Automatic shutdown at low oil level
- One point lift
 Electric starter
- Hour meter



- Crank start handle (+3kg)■ Block paving mat■ Extension plate

- Service Kit