

2 Deck Inclined Screeners

TS2300 2 Deck Screener



Specification

Max Feed	Engine	Top	Bottom	Middle
Capacity	Size	Deck	Deck	Deck
225 T/H*	JCB 84Hp (63Kw)	3.05m x 1.37m (10' x 4'6")	2.44m x 1.37m (8' x 4'6")	

^{*}Depending on material density and screen set up

Dimension Specification

Transport Dimensions			Working Dimensions		
Height	Width	Length	Width	Length	Weight (Est.)
3200mm (10' 6")	2500mm (8' 4")	13,210mm (44' 4")	14,080mm (46' 2")	14,400mm (47' 3")	19,250 Kgs (42,439 lbs)

TS2300

The TS2300 is a compact yet flexible 3 way spilt screener. Its neat design allows it to be easily transported and is ideal for areas with strict transport laws. You'll be able to easily manoeuvre this machine on site and it will fit into the most difficult of spaces.

The steep screen angle and superior performance of the screenbox ensures that this machine can screen materials exceptionally well and it is especially good at screening sand and peastone. While this machine has been compactly designed accessibility has not been compromised, for example, the large area around the powerpack allows for easy access and fast maintenance.

If you need a compact, easily portable screener that can provide you with screened material of the highest quality you'll not find any better than the TS2300.





Features & Benefits

- Superior Performance 10' x 4'6" (3.05m x 1.37m) Screenbox
- Large 7.85 yd³ (6 m³) hopper that can be fed directly by large excavators
- A compact design makes this machine easy and economical to transport
- Steep screen angles ensures a high quality screened product

