

2 Deck Inclined Screeners

TS2600 2 Deck Screener



Specification

Max Feed	Engine	Top	Bottom	Middle
Capacity	Size	Deck	Deck	Deck
650 T/H*	CAT 125Hp (93Kw)	6.10m x 1.52m (20' x 5')	5.49m x 1.52m (18' x 5')	•

^{*}Depending on material density and screen set up

Dimension Specification

Transport Dimensions			Working Dimensions		
Height	Width	Length	Width	Length	Weight (Est.)
3400mm (11' 2")	2900mm (9' 6")	18,450mm (60' 6")	18,240mm (59' 10")	18,780mm (61' 7")	36,000kgs (79,366 lbs)

TS2600

The hugely advanced TS2600 is leading the market in 20' x 5' Screeners with its High Quality, High Capacity and Low Operating Cost.

Its outstanding Production Performance, Ease of Use, Reliability and Product Quality is providing customers with fantastic returns. Due to its adjustable screenbox angles this machine is incredibly adaptable even in the toughest environments.

Made from the highest quality components, the TS2600 exceeds across a wide range of applications including Quarrying, Crusher Circuits, Sand & Gravel, Coal Screening, Topsoil and Woodchip. This machine will not let you down.





Features & Benefits

- 20' x 5' (6.1m x 1.52m) Super High Performance Screenbox
- 48" (1200mm) Feed Conveyor Ensures High Capacity Screening
- High Quality Components make this one of the most dependable machines on the market
- Highly adaptable machine that excels in a huge range of applications

