MINIDUMPER

FASTYERDINI

11600-1



ia.

TM500

7 11

FASTVERDINI

Qualità e tecnologia venduta in 60 paesi del mondo. Quality and technology in 60 countries worldwide.

MINIDUMPER TM500 mechanical

Compact machines designed for construction, agriculture and renovation works; ideal for work in the most difficult places. They are equipped with the best motion transmission systems, both hydraulically and mechanically, for a long life.

TM500DI

Minidumper with dumper and mechanical transmission

- Honda petrol engine GX 200 HP 6
- Payload capacity 500 Kg.
- 8 speeds gearbox (6 forward + 2 reverse gears)
- Hydraulic tipping
- Mechanical transmission
- Steering with mechanical disengagements
- Max. gradient capability 30%
- Rubber tracks 180x60x42 cm
- Weight 210 Kg.
- Dimensions: 1900x630x1080 mm

TM350AM - TM500AM

Minidumper agricultural version with widening side board for big volume loading

- Payload capacity 350 · 500 Kg.
- Weight 195 210 Kg.
- Dimensions: 1630x630x990 mm

TM500



MINIDUMPER IT500H

IT500H

Mini Dumper with dumper and hydrostatic transmission

- Honda petrol engine GX 200 HP 6
- Payload capacity 500 Kg.
- Platform for operator
- Hydrostatic transmission
- Orbital motors displacement 200 cc
- Hydraulic oil tank 14 l
- Skip capacity 0,21 mc3
- Double hydraulic gear pump
- Fixed displacement
- Max. pressure 180 bar
- Pump capacity 4,2+4,2 cc/rpm
- Over center valve safety system
- Max. gradient capability 30%
- Rubber tracks 180x60x42 cm
- On demand: self-loading shovel (weight + 85 Kg.)
- Weight 310 Kg.
 Dimensions: 1515x720x1230 mm





MINIDUMPER IT 600HP

hydraulic

Mini Dumper with dumper and hydrostatic transmission

- Honda petrol engine GX 270 HP 9
- Payload capacity 600 Kg.
- Operator's footboat
- Hydrostatic transmission
- Double advancement speed
- Orbital motors displacement 200 cc
- Hydraulic oil tank 14 l.
- Skip capacity 0,21 mc3
- Single hydraulic pump group 2 + three way flow divider
- Fixed displacement
- Max. pressure 180 bar
- Pump capacity 10,8 cc/rpm
 Over center valve safety system
- Max. gradient capability 30%
- Rubber tracks 180x60x42 cm
- Weight 410 Kg.
- On demand: self-loading shovel (weight + 85 Kg.)
- Dimensions:
- 1515x840x1230 mm with dumper







Concrete mixer capacity 200 I.

- With mixer and self-loading shovel. Weight 510 Kg.
- With self-loading shovel Weight 425 Kg.
- Dimensions: 2040x840x1310 mm



Macchine edili e stradali Machinery for building and roadwork 61122 Chiusa di Ginestreto Via dell'Industria · Pesaro (ITALY) Tel. +39 0721 481347

Export department: Tel. +39 0721 481374 www.fastverdini.it fastverdini@fastverdini.it