



RANGE

CT

VIBRATING WHEEL COMPACTORS

CT 2.8B

- Extremely precise and versatile
- Maximum operator comfort
- Result: solid, even and well compacted trench bottom

VIBRATING WHEEL COMPACTORS

CT 2.8 B



Designed for compacting trench bottoms,
Simex CT vibrating wheel compactors guarantee
a permanently solid, even and well compacted
bottom that ensures maximum road safety.
Perfect insulation from prime mover. Thanks
to the reverse-rotation vibrating twin shaft
positioned at center of the wheel, vertical forces
are added up and horizontal forces are countered
for increased operator comfort.

Wheel width can be adjusted via bolted sectors that are easily changed on site.

Possibility to mount the rotation allows

compaction in any position, even in the most difficult-to-reach areas.

ADVANTAGES

- Extremely precise and versatile
- Maximum operator comfort
- Result: solid, even and well compacted trench bottom

TECHNICAL DATA		CT 2.8 B
Recommended excavator weight (1)	ton /bs	5 - 9 11000 - 20000
Standard wheel		
Width of bolted sectors (mm)	mm inch	150 - 200 - 250 - 300 - 350 - 400 6 - 8 - 10 -12 -14 - 16
Working depth	mm inch	0 - 700 0 - 28
Special wheels		
Wheel width (2)	mm inch	50 - 100 2 - 4
Working depth	mm inch	0 - 350 <i>0 - 14</i>
Vibration frequency	Hz	30 - 40
Max. vertical force	kN lbf	42 9400
Operating weight (3)	kg Ibs	530 - 585 1160 - 1300
Required oil flow	l/min gpm	40 - 60 11 - 16
Max. required oil pressure	BAR psi	220 3200

- (1) The maximum operating load permitted for the excavator, when added to the weight of the standard bucket, must match or exceed the weight of the attachment.
 (2) User is responsible for ensuring that the equipment meets the excavator's specifications and weight requirements.
- z) oser is responsible for ensuring that the equipment meets the excavator's specifications are available on request.

 $Simex\ does\ not\ accept\ responsibility\ or\ liability\ for\ the\ information\ provided.\ Technical\ modifications\ may\ vary\ without\ prior\ notice.$



Backhoe

